

# Elephant electric chain hoists (DA)



## DA - 3 Phase, single speed

### Features:

- Reliable and durable limit switch
- Highly durable case hardened load chain
- Unique chain guide
- Tough durable motor
- High precision low power consumption electro-magnetic brake
- Operated by low voltage (24V) control
- Rated best electric chain hoist worldwide
- Designed to JIS 8815/1987 design standard
- Manufactured to ISO 9001 QAS
- Available 380/550V
- Ideal for extra heavy duty applications

Product Code	Model No.	Working Load Limits (tonne)	Manufacturer's test load (tonne)	No. of falls reeving	Min distance between hooks (mm)	Lifting speed (m/min) (FB) High speed/ Low speed	Lifting motor output (kW) (FB) High speed Low speed	Net Mass (kg)
A00100001	DA 2.5	2.5	3.13	1	775	5.5	3.4	128
A00100002	DA 3	3	3.75	2	990	4.35	3.4	145
A00100003	DA 5	5	6.25	2	1060	2.75	3.4	163
A00100004	DA 10	10	12.5	4	1390	2.7	3.4x2	396

### Dimensions:

Model No.	WLL (tonne)	Manufacturer's test load (tonne)	Standard lift (m)	A	B	C	D	E	F	min. H
DA-2.5	2.5	3.13	4	655	342	313	372	198	174	775
DA-3	3	3.75	3	655	342	313	372	258	114	990
DB-3	3	3.75	3	717	372	345	372	258	114	990
DA-5	5	6.25	3	655	342	313	375	273	102	1060
DA-10	10	12.5	3	684	342	342	960	373	373	1390

