

Elephant electric chain hoists (FA)

FA - 3 Phase, single speed



Features:

- Tough heavy duty motor
- 3-phase : Class E insulation
- Reliable electro-magnetic DC brake
- Highly durable load chain (case hardened)
- Totally enclosed steel plate construction
- Wiring - simple plug-in, plug out connection of wires
- Overload alarm hook (if overloaded the hook elongates without fracturing)
- IP55 rated
- Operated by low voltage (24V) control
- Designed to JIS 8815/1987 design standard
- Manufactured to ISO 9001 QAS
- Available 380/550V
- Ideal for heavy duty application
- Rated best electric chain hoists worldwide

Product Code	Model No.	Working Load Limit (tonne)	Manufacturer's test load (tonne)	No. of falls reeving	Lifting Min distance between hooks (mm)	Lifting speed (m/min) (FB) High speed/ Low speed	motor output (kW) (FB) High speed/ Low speed	Net Mass (kg)
A0010005	FA-0.5	0.5	0.63	1	542	7.0	0.9	43
A0010006	FA-1	1	1.25	1	600	6.3	1.6	56
A0010007	FA-2	2	2.5	2	776	3.1	1.6	64

Dimensions:

WLL (tonne)	A	B	C	D	K	L	M	N	O
FA 0.5t	161	124	224	311	36	26	86	24	19
FA 1t	170	128	239	348.5	43	33	107	31	23
FA 2t	133	165	239	372	53	42	144	44	30

