

Elephant manual chain blocks



Model KII

Features:

- Super strong heat treated load chain (McKinnon GR1000)
- Hooks of easier handling shape (i.e. opening of hooks wider for easier handling)
- Tough gear case reinforced with four ribs and four knock pins
- Rolled edge hand wheel cover (allows for smooth operation when pulled at a slant)
- Strong anti corrosive electrostatic powder coating.
- Wet friction discs for longer life
- Unique chain guide
- Anchor plate to avoid over lifting / lowering
- Very light and compact (11.4kg / 1 tonne)
- Designed to JIS B8802/12 design standard
- Manufactured to ISO 9001 QAS
- Rated best chain block worldwide

| Product Code | Model | Working Load Limit (tonne) | Standard lift (m) | Manufacturer's test load (tonne) | Head-room (mm) | Hand effort to lift full working load (kgf) | Load chain no. of falls | Net Mass (kg) |
|--------------|---------|----------------------------|-------------------|--|----------------|---|-------------------------|---------------|
| A00200013 | KII-0.5 | 0.5 | 3 | 150% x max. working load 125% x max. working load | 275 | 27 | 1 | 9 |
| A00200014 | KII-1 | 1 | 3 | | 300 | 31.5 | 1 | 11.4 |
| A00200015 | KII-1.6 | 1.6 | 3 | | 335 | 41.5 | 1 | 14.7 |
| A00200016 | KII-2 | 2 | 3 | | 375 | 40 | 1 | 21 |
| A00200021 | KII-3 S | 3 | 3 | | 410 | 40.5 | 1 | 25.4 |
| A00200018 | KII-3.1 | 3.1 | 3 | | 530 | 47.5 | 2 | 24 |
| A00200019 | KII-5 | 5 | 3 | | 625 | 48 | 2 | 39.5 |
| A00200020 | KII-10 | 10 | 3 | | 775 | 52.5 | 4 | 82 |

Dimensions:

| WLL (tonne) | A | B | C | D | E | F |
|-------------|-----|-------|-----|------|----|----|
| KII - 0.5 | 140 | 155 | 58 | 33 | 26 | 36 |
| KII - 1 | 160 | 160 | 62 | 35 | 30 | 43 |
| KII - 1.6 | 183 | 167.5 | 65 | 37 | 35 | 48 |
| KII - 2 | 215 | 183 | 66 | 41 | 38 | 53 |
| KII - 3S | 233 | 190 | 70 | 44 | 40 | 55 |
| KII - 3.1 | 230 | 167.5 | 110 | 62.5 | 44 | 60 |
| KII - 5 | 282 | 190 | 166 | 78.5 | 53 | 70 |
| KII - 10 | 385 | 190 | 300 | 98 | 70 | 85 |

