

# Max-alloy Gr.8 Typical Sling Types

## SINGLE CHAIN SLINGS



Style A

TYPE SOS  
SINGLE  
ADJUSTABLE




TYPE SOG  
GRAB  
HOOK




TYPE SOG  
CLEVIS  
GRAB HOOK




TYPE SOS  
CLEVIS  
SAFETY HOOK



TYPE SOF  
FOUNDRY  
HOOK




TYPE SOS  
SAFETY  
HOOK




TYPE SOSL  
SELF-LOCKING  
HOOK

## DOUBLE CHAIN SLINGS




SINGLE  
BASKET




Style B


TYPE DOS  
DOUBLE  
ADJUSTABLE




TYPE DOG  
CLEVIS  
GRAB HOOK



TYPE DOS  
SAFETY HOOK




TYPE DOF  
FOUNDRY HOOK




TYPE DOSL  
SELF-LOCKING


## TRIPLE & QUAD CHAIN SLINGS



DOUBLE BASKET




TYPE TOSL  
SELF-LOCKING  
HOOK




TYPE QOS  
SAFETY HOOK

## SINGLE ADJUSTABLE LOOP CHAIN SLING




Style A




Style B

SINGLE ADJUSTABLE LOOP



Style A



Style B

DOUBLE ADJUSTABLE LOOP

## DOUBLE ADJUSTABLE LOOP CHAIN SLING

Scan Metals Group Max Alloy complies fully with SABS 7593 for "Instant" assembled chain slings and to SABS 4778 for "Welded" chain sling assemblies, and with the requirements of EN 818- 1 & 4.