

# Tusker® chain tie down equipment



## Grab Hook - Grade 5

Product Code	Chain size	W	D	H	L	P	R	Mass ea
	mm	mm	mm	mm	mm	mm	mm	kg
F10525085	10.0	11	68	12.7	114	11	68	0.5
F10525086	13.0	15	84	16.7	143	14	85	0.9



## Slip Hook - Grade 5

Product Code	Chain size	W	D	H	L	P	R	Mass ea
	mm	mm	mm	mm	mm	mm	mm	kg
F10525087	10.0	11	89	32.0	124	11	76	0.6
F10525088	13.0	15	124	44.5	162	14	100	1.3



## Tension selector: The new ratchet binder

- Continuous take-up feature with infinite adjustment
- One piece assembly, no bolts and nuts to loosen. Ratchet spring rust proofed.
- All load bearing or holding parts forged
- Eye bolts and Hooks are alloy steel, quenched and tempered.
- Easy to operate-positive ratchet.


Product Code	Model No.	Chain Size	Handle Length	Barrel Length	Take-up	Minimum Breaking Strength	Mass
		mm	mm	mm	mm	kg	kg
F10625094	R-A	10.0/13.0	356	254	200	15 000	5.6



## Lever Binder

- Drop forged and heat treated
- Each binder is proof tested

Product Code	Chain Size	Handle Length	Take-up	Minimum Breaking Strength	Mass
	mm	mm	mm	kg	kg
F10625091	6.3	286	64	2 830	1.13
F10625092	10.0	405	102	8 620	3.50
F10625093	13.0	470	115	12 700	5.10



## 28mm Turnbuckle

The typical Chain Assembly incorporating the Turnbuckle consists of a 10m length of chain with a Grab Hook attached at one end and a short length of 600mm of chain with a Slip Hook attached at the other end of the turnbuckle.

Product Code	Minimum Size	Maximum Length	Take-up	Minimum Breaking Strength	Mass each
	mm	mm	mm	kg	kg
F10625095	610	890	280	13 600	7

