

Generally in accordance with EC machinery directives EEC 89/392/EEC, 91/368/EEC



Palletfork - Model PGA (Std ISO Pallet)

- Gives any crane pallet handling capability quickly and safely
- Automatic load levelling
- Service free - sturdy construction made of german steel
- Special designs on request - eg. double, extra height etc.
- Standard configuration - 1100 depth x 1200 width x 1100 height

Product Code	Model	Working Load Limit
BO2305033	PGA20	WLL - 2 000kg
BO2305034	PGA30	WLL - 3 000kg



Palletfork - Model PGM (Std ISO Pallet)

- Special designs on request - eg. double, extra height etc.
- Gives any crane pallet handling capability
- Pre-selection of load tilt
- Service free - sturdy construction
- 1100 depth x 1200 width x 1100 height

Product Code	Model	Working Load Limit
BO2305035	PGM20	WLL - 2 000kg
SPECIAL	PGM30	WLL - 3 000kg



"T" Hook - Storm water pipe handling and installation

- Superquick pipe engagement/disengagement from the outside
- Supplied complete with 1.5m adjustable chain sling

NOTE: No side (angular) lifting permitted.

Product Code	Model	Working Load Limit (vertical lift)
BO2205029	T250	WLL - 2500kg
BO2205030	T500	WLL - 5000kg



Manhole installation clamp set

- **The only way** to handle/install manhole sections.
Quick to engage and disengage with complete safety.

Product Code	Model	WLL & Wall Thickness Range
BO2105025	T180	1 800kg - 60-120mm
BO2105026	T350	3 500kg - 120-180mm