



Type	Capacity/ colour	Working load limits for 1 lifting sling					Working load limits for 2 lifting slings				
		Straight	Chocked	0°-7°	7°-45°	45°-60°	7°-45°	7°-45°	45°-60°	45°-60°	
		1	0.8	2	1.4	1	1.4	1.12	1	0.8	
DFS 30/50	WLL 1 t PURPLE	1000	800	2000	1400	1000	1400	1120	1000	800	
DFS 60	WLL 2 t GREEN	2000	1600	4000	2800	2000	2800	2240	2000	1600	
DFS 75	WLL 2.5 t OLIVE GREEN	2500	2000	5000	3500	2500	3500	2800	2500	2000	
DFS 90	WLL 3 t YELLOW	3000	2400	6300	4200	3000	4200	3360	3000	2400	
DFS 120	WLL 4 t GREY	4000	3200	8000	5600	4000	5600	4480	4000	3200	
DFS 150	WLL 5 t RED	5000	4000	10000	7000	5000	7000	5600	5000	4000	
DFS 180	WLL 6 t BROWN	6000	4800	12000	8400	6000	8400	6720	6000	4800	
DFS 240	WLL 8 t BLUE	8000	6400	16000	11200	8000	11200	8960	8000	6400	
DFS 300	WLL 10 t ORANGE	10000	8000	20000	14000	10000	14000	11200	10000	8000	

## Features

- Manufactured according to Machine Directive 89/392/EC
- Duplex (for double safety) lifting sling made from high tenacity polyester fibres
- Colourcoded according to EN 1492-1/ SANS 94-1 2003
- Temperature range of -40°C to +100°C
- Available in any length

## PROTECTION SLEEVES:

- Extreme conditions: "Stobitex": - steel plates/coils, polyurethane bonded or sleeve
- Hard conditions: "Polytex" - concrete/granite, polyester sleeve
- Moderate conditions: "PVC" - wood, PVC layflat sleeve

