

Tusker® snatch and vertical lead block



Vertical Lead Block

- Available painted or galvanised.
- Fitted with steel sheaves.
- Self-Lubricated Bronze Bushes
- Available in bigger sizes
- Also available to customers' specification

Sheave dia mm	Resulting working load limit tonne	Wire rope dia mm	Mass each kg	Dimensions			
				C	D	E	F
150	2	10	5	88	150	138	175
200	2 1/2	13	12	122	200	170	245
250	3	16	15	160	250	195	295
300	4	19	30	182	300	150	135
350	5	22	50	220	350	225	450



Snatch Blocks

- Available in capacities of up to 40 000 kg
- Grease nipples for positive greasing
- Test certificates supplied
- All steel construction
- Suitable for steel wire rope
- Hinged side to fit rope
- Also available with swivel oval eye
- Phosphor bronze bushed sheaves

Product Code	Sheave dia mm	Rope dia mm	W.L.L. *(tonne)	Mass ea kg
K20150018	100	10-13	0.5	4
K20150019	125	10-13	1.0	5
K20150020	150	10-13	2.0	7
K20150021	200	13-16	3.0	19
K20150022	250	16-20	5.0	32
K20150023	300	16-20	7.5	40
K20150024	350	20-22	10.0	70

