

Tusker® swivels



Eye/Eye

- **Material** : High tensile steel, quenched and tempered
- **Safety Factor** : 5 times W.L.L. = minimum breaking strength
- **Finish** : Galvanized

Size	Working Load Limit	A	B	C	D	R	Approx Mass per pce
mm	tonne	mm	mm	mm	mm	mm	kg
6	0.39	32	17	19	27	75	0.10
8	0.57	41	21	25	32	90	0.18
10	1.02	51	24	32	38	110	0.31
13	1.6	64	33	38	51	138	0.65
16	2.4	76	40	44	60	167	1.08
19	3.3	89	44	51	67	183	1.79
22	4.5	102	52	57	78	213	2.80
25	5.7	114	59	64	89	245	4.06
32	8.2	143	68	79	94	283	7.60
38	20.5	178	106	102	106	435	22.30



Eye/Clevis

- **Material** : High tensile steel, quenched and tempered
- **Safety Factor** : 5 times W.L.L. = minimum breaking strength
- **Finish** : Galvanized

Size	Working Load Limit	A	B	C	K	N	P	R	Approx Mass per pce
mm	tonne	mm	mm	mm	mm	mm	mm	mm	kg
6	0.39	32	17	19	12	22	6	67	0.11
8	0.57	41	21	25	13	22	8	75	0.17
10	1.02	51	24	32	16	27	10	92	0.32
13	1.6	64	33	38	19	33	13	114	0.65
16	2.4	76	40	44	24	38	16	135	1.12
19	3.3	89	44	51	29	44	19	154	1.88
22	4.5	102	52	57	30	52	22	178	2.21
25	5.7	114	59	64	44	71	29	217	4.87
32	8.2	143	68	79	52	71	35	240	7.38
38	20.5	178	106	102	73	113	57	375	22.20

