



# Tusker® solid thimbles



- Available in drilled or blank form



Product code	Rope dia	Q	B	C	E	F (min)	G	M (max)
	mm	mm	mm	mm	mm	mm	mm	mm
I16240090	8	25	34	11	49	8	5	13
I16240091	10	32	44	14	57	11	6	18
I16240092	12	38	52	18	70	13	7	21
I16240093	14	44	60	21	82	14	8	22
	16	52	70	22	95	16	10	28
	18	57	78	25	105	19	11	28
I16240094	21	64	85	28	118	21	11	34
I16240095	22	70	95	32	127	22	13	37
I16240096	24	76	105	33	140	25	14	40
I16240097	26	82	115	36	152	26	16	43
I16240098	28	89	125	39	166	28	18	46
I16240100	32	102	140	44	192	33	19	51
I16240101	36	115	155	52	209	38	21	59
I16240102	40	127	172	57	234	41	22	66
I16240104	44	140	190	64	260	44	25	70



# Tusker® thimbles



G-6170

Generally to BS 464

- **Material** : mild steel.
- **Finish** : galvanized



Product Code	Dia rope	Groove width	Overall length	Inside length	Inside width	Back thickness	Approx. Mass
		a	B	L	c	s	per 100 pcs
	mm	mm	mm	mm	mm	mm	kg
I16240067	3	4	26	21	13	1.6	0.8
I16240068	5	6	38	25	16	2.4	1.6
I16240069	6	7	44	28	18	2.4	1.9
I16240070	8	8	54	33	22	4	5.7
I16240071	10	10	64	38	25	4.8	7.6
I16240072	13	14	80	44	32	5.6	18.9
I16240073	16	16	98	59	41	7.9	34
I16240074	19	21	124	73	51	9.5	62.4
I16240075	22	22	133	83	57	9.5	75.6
I16240076	25	27	162	108	70	10.3	124.7
I16240077	28	29	178	111	76	12.7	151
I16240079	32	33	197	133	95	12.7	204
I16240080	35	38	229	152	105	15.9	318
I16240082	38	41	254	165	114	17.5	488
I16240083	41	43	254	165	114	17.5	499
I16240085	44	51	286	178	127	25.4	556
I16240086	47	60	318	191	133	28.6	-
I16240088	50	64	330	203	140	28.6	-