

# Tusker® thrust bearing swivels

- **Material** : Carbon steel
- **Safety factor** : 5 times WLL = minimum breaking strength
- **Finish** : Yellow painted
- Swivels for all safe working loads are available in any of the configurations illustrated.
- Swivels have been individually proof tested.



Type	Working load limit	Total length	Thick-ness eye	Outside dia	Outside jaw width	Inside jaw width	Hole in jaw	Hole in eye	Approx. Mass per pce									
										tonne	mm	mm	mm	mm	mm	mm	mm	kg
										A	B	C	D	E	F	G		
H-J	3	273	-	75	41	20	20	-	5									
E-J	3	203	20	75	41	20	20	23	4									
J-J	3	210	-	75	41	20	20	-	4.5									
H-E	3	270	20	75	-	-	-	23	4.5									
J-E	3	203	20	75	41	20	20	23	4									
E-E	3	200	20	75	-	-	-	23	3.6									
H-J	5	337	-	95	57	25	23	-	9.5									
E-J	5	244	25	95	57	25	23	32	7.7									
J-J	5	251	-	95	57	25	23	-	8.2									
H-E	5	330	25	95	-	-	-	32	9									
J-E	5	244	25	95	57	25	23	32	7.7									
E-E	5	238	25	95	-	-	-	32	6.8									
H-J	7.5	457	-	121	70	35	29	-	20.8									
E-J	7.5	318	32	121	70	35	29	35	16									
J-J	7.5	330	-	121	70	35	29	-	16.3									
H-E	7.5	448	32	121	-	-	-	35	20.4									
J-E	7.5	321	32	121	70	35	29	35	16									
E-E	7.5	308	32	121	-	-	-	35	15									
H-J	10	479	-	121	75	44	38	-	24									
E-J	10	362	44	121	75	44	38	41	18.6									
J-J	10	378	-	121	75	44	38	-	18.6									
H-E	10	470	44	121	-	-	-	41	24									
J-E	10	368	44	121	75	44	38	41	19									
E-E	10	352	44	121	-	-	-	41	18									
H-J	15	578	-	140	89	44	38	-	36									
E-J	15	429	51	140	89	44	38	51	30									
J-J	15	448	-	140	89	44	38	-	29									
H-E	15	568	51	140	-	-	-	51	35									
J-E	15	438	51	140	89	44	38	51	30									
E-E	15	419	51	140	-	-	-	51	28									

