


Tusker® Duplex Flat Slings (DFS strips)

Type	Capacity/ Colour	Straight	Chocked	Working Load Limits for 1 Lifting Sling						Working Load Limits for 2 Lifting Slings							
				0°-7°		7°-45°		45°-60°		7°-45°		45°-60°		45°-60°			
				1	2	1.4	1400	2800	1000	1.4	1400	2800	1.12	1120	2240	1	1000
DFS 50	1000kg															0.8	800
DFS 60	2000kg															1	1000
DFS 90	3000kg															1.12	1120
DFS 120	4000kg															1.4	1400
DFS 150	5000kg															1.4	1400
DFS 180	6000kg															1.4	1400
DFS 240	8000kg															1.4	1400
DFS 300	10 000kg															1.4	1400



Features:

- Duplex (for double safety) lifting sling made from high tenacity polyester fibres
- Manufactured in accordance with EN 1492-1/ SANS 94-1 2003 (F.O.S. 7:1)
- Temperature range of -40°C to +100°C
- Available in any length up to 50t WLL
- Double stitching with reinforced eyes

Protection Sleeves

- Extreme conditions: "Stobitex" : - steel plates/coils, polyurethane bonded or sleeve
- Hard conditions: "Polytex" - concrete/granite, polyester sleeve
- Moderate conditions: "PVC" - wood, PVC layflat sleeve

