



6x36 WS = 6x[1+7+(7+7)+14] FC

Features:

- Galvanised rope lubricated with light lubrication A1 or dry
- Ungalvanised rope lubricated with lubrication - A1
- Also used for the manufacture of slings
- All rope manufactured generally to EN 12385
- Supplied with manufacturer's certificate of conformance
- Available in left or right hand lay
- Suitable for overhead gantry cranes

Rope Diameter (mm)	Unit Weight kg/m	Wire Tensile	
		1770 N/mm ²	1960 N/mm ²
		Minimum Breaking Load (MBL) kN	
8.00	0.235	37.4	41.4
10.00	0.367	58.4	64.7
12.00	0.528	84.1	93.1
13.00	0.620	98.7	109.3
14.00	0.719	114	127
16.00	0.940	150	166
18.00	1.189	189	210
19.00	1.325	211	233
20.00	1.468	234	259
22.00	1.776	283	313
24.00	2.114	336	373
26.00	2.481	395	437
28.00	2.877	458	507
32.00	3.758	598	662
36.00	4.756	757	838
38.00	5.299	843	934
40.00	5.872	935	1035
42.00	6.474	1030	1141
44.00	7.105	1131	1252
48.00	8.456	1346	1490
50.00	9.175	1460	1617
52.00	9.924	1579	1749
56.00	11.509	1832	
60.00	13.910	2201	
64.00	15.820	2507	