


# Tusker® Solid Thimbles

## Available in Drilled or Blank Form




Product code	Rope Dia (mm)	Q (mm)	B (mm)	C (mm)	E (mm)	F (mm)	G (mm)	M (max) (mm)
h6240090	8	25	34	11	49	8	5	17
h6240091	10	32	44	14	57	11	6	18.5
h6240092	12	38	52	18	70	13	7	21.5
h6240093	14	44	60	21	82	14	8	22
	16	52	70	22	95	16	10	28.5
h6240094	18	57	78	25	105	19	11	28
	20	64	85	28	118	21	11	35.5
h6240095	22	70	95	32	127	22	13	38
h6240096	24	76	105	33	140	25	14	40
h6240097	26	82	115	36	152	26	16	43
h6240098	28	89	125	39	166	28	18	46
h6240100	32	102	140	44	192	33	19	52
h6240101	36	115	155	52	209	38	21	60
h6240102	38	127	172	57	234	41	22	-
h6240103	40	138	190	60	260	43	25	66
h6240104	44	140	200	64	280	44	29	70

# Tusker® Thimbles

## Generally to BS 464

- Material: mild steel
- Finish: galvanized



Product Code	Rope Dia (mm)	Groove Width (mm)	Overall Length (mm)		Inside Length (mm)		Back Thickness (mm)	Approx Mass per 100 pcs Kg
			A	B	L	C		
h6240067	3	4	26	21	13	1.6	0.8	
h6240068	5	6	38	25	16	2.4	1.6	
h6240069	6	7	44	28	18	2.4	1.9	
h6240070	8	8	54	33	22	4	5.7	
h6240071	10	10	64	38	25	4.8	7.6	
h6240072	13	14	80	44	32	5.6	18.9	
h6240073	16	16	98	59	41	7.9	34	
h6240074	19	21	124	73	51	9.5	62.4	
h6240075	22	22	133	83	57	9.5	75.6	
h6240076	25	27	162	108	70	10.3	124.7	
h6240077	28	29	178	111	76	12.7	151	
h6240079	32	33	197	133	95	12.7	204	
h6240080	35	38	229	152	105	15.9	318	
h6240082	38	41	254	165	114	17.5	488	
h6240083	41	43	254	165	114	17.5	499	
h6240085	44	51	286	178	127	25.4	556	
h6240086	47	60	318	191	133	28.6	-	
h6240088	50	64	330	203	140	28.6	-	