

# Tusker® Thrust Bearing Swivels

- Material: Carbon steel
- Safety factor: 5 times WLL = minimum breaking strength
- Finish: Yellow painted
- Swivels for all safe working loads are available in any of the configurations illustrated.
- Swivels have been individually proof tested.



Type	Working Load Limit	Total Length	Thickness Eye	Outside Dia	Outside Jaw Width	Inside Jaw Width	Hole in Jaw	Hole in Eye	Appros Mass per pce
	Tonne	mm	mm	mm	mm	mm	mm	mm	kg
		A	B	C	D	E	F	G	
H-J	3	273	-	75	41	20	20	-	5
E-J	3	203	20	75	41	20	20	23	4
J-J	3	210	-	75	41	20	20	-	4.5
H-E	3	270	20	75	-	-	-	23	4.5
J-E	3	203	20	75	41	20	20	23	4
E-E	3	200	20	75	-	-	-	23	3.6
H-J	5	337	-	95	57	25	23	-	9.5
E-J	5	244	25	95	57	25	23	32	7.7
J-J	5	251	-	95	57	25	23	-	8.2
H-E	5	330	25	95	-	-	-	32	9
J-E	5	244	25	95	57	25	23	32	7.7
E-E	5	238	25	95	-	-	-	32	6.8
H-J	7.5	457	-	121	70	35	29	-	20.8
E-J	7.5	318	32	121	70	35	29	35	16
J-J	7.5	330	-	121	70	35	29	-	16.3
H-E	7.5	448	32	121	-	-	-	35	20.4
J-E	7.5	321	32	121	70	35	29	35	16
E-E	7.5	308	32	121	-	-	-	35	15
H-J	10	479	-	121	75	44	38	-	24
E-J	10	362	44	121	75	44	38	41	18.6
J-J	10	378	-	121	75	44	38	-	18.6
H-E	10	470	44	121	-	-	-	41	24
J-E	10	368	44	121	75	44	38	41	19
E-E	10	352	44	121	-	-	-	41	18
H-J	15	578	-	140	89	44	38	-	36
E-J	15	429	51	140	89	44	38	51	30
J-J	15	448	-	140	89	44	38	-	29
H-E	15	568	51	140	-	-	-	51	35
J-E	15	438	51	140	89	44	38	51	30
E-E	15	419	51	140	-	-	-	51	28

